

From raw milk
to cream



SEPARATOR SP

For making cream and skimmed milk



Add value to milk

Making cream and skimmed milk



- **Controlled process**
 - regulation of fat content in cream and skimmed milk with a regulating screw
- **Process repeatability**
 - the precisely designed and produced machine ensures process repeatability
- **Great efficiency**
 - brushless motor ensures a long lifecycle
 - 80–95 % of energy converted to motor power
- **Simple maintenance**
 - the shape and the treatment of surfaces enable simple cleaning
 - materials conform to applicable standards

- 1 Raw milk container.** Optimal temperature of raw milk is between 30 and 40 °C.
- 2 Cream outlet.** Depending on fat content in raw milk and on adjustment with the regulating screw, 10–20 % of cream can be produced.
- 3 Skimmed milk outlet.** Fat content in skimmed milk is less than 0.5 %.
- 4 Stable support.** Wide rubber legs ensure device stability.



Technical information



Type	Hourly capacity (l/h)	Milk container capacity (l)	Power supply	Motor power (W)	Milk inlet height (mm)	Product weight (kg)
SP 130	130	10	230V 1N 50Hz	70	540	5
SP 315	315	22	230V 1N 50–60Hz	150	920	16
SP 600	580	45	230V 1N 50Hz	400	1050	24



PLEVNIK, d.o.o.
 Podsmreka 56
 SI 1356 Dobrova
 info@plevnik.si
 + 386 (0)1 200 60 80

Together we have created
 more than 5,000
 successful business stories.



www.plevnik.si

Representative: